

# ETF 7MM HYBRID FLOORING

## TECHNICAL SPECIFICATIONS

- ✓ German Click System
- ✓ 100 % Waterproof
- ✓ Durable and Colour & Pattern Consistent

### DIMENSION

1500mm X 228mm X 7mm

### INSTALLATION METHOD

Floating Floor (Licensed Click System)

### BOX CONTAINS

6 Planks = 2.052 m<sup>2</sup> / box

### WEAR RESISTANCE PROFILE

3um Urethane UV Layer

### SLIP RATING

AS 4586 (2013) Slip Resistance Classification of new Pedestrian Surface Materials

Wet Pendulum Test Method  
Achieved a pass of P3

### ENVIRONMENTAL & QUALITY CERTIFICATES

E0 EN Emission Approved  
ISO 14001:2015 Environmental System Approved  
ISO 9001:2015 Quality System Approved

### FIRE RATING

(CHF) Critical Heat / Radiant Flux  
(AS ISO 9239.1:2003)

Pass the 9239.1 standards as required by the Australian National Construction Code

### ACOUSTIC RATING

Achieved AAAC 5 Star Acoustic Rating

### WARRANTY

25 Years Residential Use & 5 Years Commercial Use  
(Please refer to the ETF Laminate product warranty)

#### VINYL WEAR LAYER

Hardened Vinyl Wear layer provide Excellent Resistance to scruff and abrasions

#### SPC RIGID CORE

100% phthalate-free extruded closed-cell core provide exceptional stability rigidity, dimensional stability and anti-telegraphing performance

#### QUITE INTEGRATED SOUND REDUCTION UNDERLAYMENT

Bonded cross-linked underlayment minimise impact and transmitted sound, provides underfoot warmth and comfort, and mitigates subfloor imperfections

#### URETHANE WITH CERAMIC BEAD FINISH

UV cured Urethane and ceramic bead top coating for enhanced durability and stain resistance

#### HD DECORATIVE FILM

High Definition film prints create vivid natural wood, stone, and abstract looks

#### UNICLIC LOCKING SYSTEM

Innovative locking system enables quick, easy, hassle-free installation



Slip Resistant



Easy to Maintain



Glue-Free Installation



Abrasion Resistant



Impact Resistant



UV Resistant



Stain Resistant



100% Waterproof



Resistant to Cigarette Ash

Combining quality & environmental control standards throughout the manufacturing process.



International Organization for Standardization



Note: Colour variation from the actual product to the electronic and printed media is to be expected.  
For detailed maintenance & Installation guidelines, please refer to the website