

ETF 9MM HYBRID FLOORING TECHNICAL SPECIFICATIONS

- ✓ German Click System
- ✓ 100 % Waterproof
- ✓ Durable and Colour & Pattern Consistent

DIMENSION

1810mm X 228mm X 9mm

INSTALLATION METHOD

Floating Floor (Licensed Click System)

BOX CONTAINS

4 Planks = 1.65072 m² / box

WEAR RESISTANCE PROFILE

5um Urethane Ceramic Layer

SLIP RATING

AS 4586 (2013) Slip Resistance Classification of new Pedestrian Surface Materials

Wet Pendulum Test Method
Achieved a pass of P3

ENVIRONMENTAL & QUALITY CERTIFICATES

E0 EN Emission Approved
ISO 14001:2015 Environmental System Approved
ISO 9001:2015 Quality System Approved

FIRE RATING

(CHF) Critical Heat / Radiant Flux
(AS ISO 9239.1:2003)

Pass the 9239.1 standards as required by the Australian National Construction Code

ACOUSTIC RATING

Achieved AAAC 5 Star Acoustic Rating

WARRANTY

25 Years Residential Use & 5 Years Commercial Use
(Please refer to the ETF Laminate product warranty)

VINYL WEAR LAYER

Hardened Vinyl Wear layer provide Excellent Resistance to scuff and abrasions

SPC RIGID CORE

100% phthalate-free extruded closed-cell core provide exceptional stability rigidity, dimensional stability and anti-telegraphing performance

QUITE INTEGRATED SOUND REDUCTION UNDERLAYMENT

Bonded cross-linked underlayment minimise impact and transmitted sound, provides underfoot warmth and comfort, and mitigates subfloor imperfections

MULTI-MELANIN with CERAMIC BEAD FINISH

Multi-melanin compound and ceramic bead top coating for extreme durability and stain resistance

HD DECORATIVE FILM

High Definition film prints create vivid natural wood, stone, and abstract looks

UNICLIC LOCKING SYSTEM

Innovative locking system enables quick, easy, hassle-free installation



Slip Resistant



Easy to Maintain



Glue-Free Installation



Abrasion Resistant



Impact Resistant



UV Resistant



Stain Resistant



100% Waterproof



Resistant to Cigarette Ash

Combining quality & environmental control standards throughout the manufacturing process.



International
Organization for
Standardization



Note: Colour variation from the actual product to the electronic and printed media is to be expected.
For detailed maintenance & Installation guidelines, please refer to the website